



2012 Downtown 300i

The Downtown 300i was designed and built for an enjoyable commute! With the open road performance of a maxi scooter and sport bike agility, the Downtown 300i delivers the ultimate scooter riding experience. This new entry in the KYMCO scooter family is powered by an all new 4-valve Electronic Fuel Injected engine coupled to an agile, responsive, light weight dual cradle steel chassis. The onboard carrying capacity of the Downtown 300i offers all the space for your daily commuting needs with a lighted, under seat storage space big enough for two helmets and a watertight console compartment for cell phone storage equipped with a 12V accessory outlet right at your fingertips. Add an optional top case and your daily commuter ride turns into a weekend touring machine.



Engine type	Liquid Cooled, Single Cylinder, 4 Stroke
Displacement	298.9 cc
Bore & stroke	72.7 x 72 mm
Compression Ratio	10.8 : 1
Valve Train	S.O.H.C., Chain Drive
Fuel Delivery	EFI
Transmission	Automatic CVT
Front Suspension	Telescopic Forks
Rear Suspension	Dual Shock
Tires	120/80-14 Front; 150/70-13 Rear
Brakes Front	Disk
Rear	Disk
Seat height	77.5 cm
Wheel base	154.4 cm
Fuel capacity	12.5 litres
Dry weight	166.5 kg
Available Colors:	

Additional Features: Modern colour schemes, electronic fuel injection, front and rear disk brakes, integrated passenger grips, center hook, illuminated under seat storage with room for 2 helmets, watertight in dash storage compartment with 12v accessory outlet for cell phones, digital instrument cluster, windscreen, dual beam quartz halogen head lights, integrated passenger pegs, 5 position adjustable rear shocks, 5 in 1 magnetic key lock system, sturdy center stand, spring assisted side stand, 12.5 litre fuel capacity.

Available Accessories:

- Scooter Cover
- Wireless Brake Light

*Please contact your local authorized KYMCO dealer for a range of other aftermarket accessories.

All KYMCO Scooters come with a 2 year limited warranty!





2012 Downtown 300i

Engine Type	Liquid Cooled, Single cylinder, 4 Stroke
Displacement	298.9 cc
Bore & stroke	72.7 x 72 mm
Compression ratio	10.8 :1
Valve train	S.O.H.C., Chain Drive
Fuel Delivery	Electronic Fuel Injection
Ignition	Electronic Fuel Injection
Transmission	Automatic CVT
Spark plug	CR7E (NGK)
Emission	CEPA Environmental Registered
Fuel capacity	12.5 litres
Tires	120/80-14 Front; 150/70-13 Rear
Front Suspension	Telescopic Forks
Rear Suspension	Swing Arm
Front Brakes	Disk
Rear Brakes	Disk
Instrument cluster	Analog Speedometer & Tachometer, Digital Odometer, Digital Clock, Low Fuel Indicator, Light Indicator, Digital Coolant Temperature Light, Maintenance Light, Oil Pressure Light, Low Battery Light
Stands	Centre and Side Stand
Storage compartment	Under Seat Compartment for two full faced helmets
Complete Size (L x W x H)	2200 x 810 x 1150 mm
Seat Height	775 mm
Dry weight	166.5 kg
Maximum Passengers	2
Warranty	Two Year Limited Warranty

